



# Pewag O.T.R. Chains

Designed for Plows, Scrapers, Loaders, Graders, and Backhoes

Pewag "All-Square" alloy equipment chains - proven value with 32% better traction and four times the wear compared to conventional twist link tire chains used in similar conditions.

(Ask about special order with swivel hooks)

**Pewag Single Spaced OTR**



**Swivel Hook**

**Pewag Double Spaced OTR**



•For more information see: **PAGE 31**

**PEWAG HEAVY EQUIPMENT**

Pewag OTR Chain											
Tire Size	Stock Number	8.2 mm	Weight Per Pair	10 mm	Weight Per Pair	12 mm	Weight Per Pair	Cross Chain	8.2 mm	10 mm	12 mm
13.00-24; 14.00-20/21; 15.5-25; 445/95-25	E2612S	•	97 lbs	•	128 lbs	•	172 lbs	E6630	•	•	•
14.00-24; 14.00-25; 385/95-24; 385/95-25	E2615S	•	114 lbs	•	148 lbs	•	184 lbs	E6630	•	•	•
16.00-20/21; 17.5-25; 445/80-25	E2624S			•	150 lbs	•	193 lbs	E6640		•	•
16.00-24; 16.00-25; 19.5L-24; 445/95-25	E2627S			•	170 lbs	•	220 lbs	E6640		•	•
20.5-25; 525/80-25	E2633S			•	182 lbs	•	261 lbs	E6650		•	•
18.00-25; 18.00-26; 505/95-25; 550/65-25	E2636S			•	188 lbs	•	243 lbs	E6650		•	•
18.00-33; 600/65-25	E2642S			•	232 lbs	•	296 lbs	E6650		•	•
23.5-25; 25.5-25; 605/80-25	E2645S			•	212 lbs	•	268 lbs	E6660		•	•
21.00-24; 21.00-25	E2648S			•	242 lbs	•	298 lbs	E6660		•	•
21.00-35	E2654S			•	292 lbs	•	351 lbs	E6660		•	•
26.5-25; 686/80-25	E2657S			•	271 lbs	•	346 lbs	E6670		•	•
24.00-25; 26.5-29	E2660S			•	304 lbs	•	356 lbs	E6670		•	•
29.5-25	E2672S			•	312 lbs	•	403 lbs	E6680		•	•
29.5-29	E2675S			•	330 lbs	•	427 lbs	E6680		•	•