

Glacier O.T.R. Chains

Designed for Plows, Scrapers, Loaders, Graders, and Backhoes

Glacier Square Link Alloy OTR



Glacier Twist Link OTR



Glacier V-Bar OTR



Glacier Double Spaced OTR



Glacier O.T.R. equipment chains are available in three different styles: twist link, square link, and V-Bar. Double link spacing is available upon request.

Glacier Twist Link OTR				Glacier V-Bar Twist Link OTR		
Tire Size	Twist Link Stock No.	Weight Per Pair	Cross Chain Stock No.	V-Bar Stock No.	Weight Per Pair	Cross Chain Stock No.
13.00-24; 14.00-20/21; 15.5-25; 445/95-25	H2612S	112lbs	H6630	H2912S	128 lbs	H6930
14.00-24; 14.00-25; 385/95-24; 385/95-25	H2615S	130 lbs	H6630	H2915S	148 lbs	H6930
16.00-20/21; 17.5-25; 445/80-25	H2624S	158 lbs	H6640	H2924S	177 lbs	H6940
16.00-24; 16.00-25; 19.5L-24; 445/95-25	H2627S	176 lbs	H6640	H2927S	203 lbs	H6940
20.5-25; 525/80-25	H2633S	194 lbs	H6650	---	---	---
18.00-25; 18.00-26; 505/95-25	H2636S	206 lbs	H6650	---	---	---
18.00-33; 600/65-25	H2642S	247 lbs	H6650	---	---	---
23.5-25; 25.5-25; 605/80-25	H2645S	354 lbs	H6660	---	---	---
21.00-24; 21.00-25	H2648S	380 lbs	H6660	---	---	---
21.00-35	H2654S	440 lbs	H6660	---	---	---
26.5-25; 686/80-25	H2657S	438 lbs	H6670	---	---	---
24.00-25; 26.5-29	H2660S	461 lbs	H6670	---	---	---
29.5-25	H2672S	489 lbs	H6680	---	---	---
29.5-29	H2675S	516 lbs	H6680	---	---	---

Glacier Square Link OTR							
Tire Size	Square Link Stock No.	8 mm	Weight Per Pair	10 mm	Weight Per Pair	12 mm	Weight Per Pair
13.00-24; 14.00-20/21; 15.5-25; 445/95-25	H2712SL	•	96 lbs	•	127 lbs		
14.00-24; 14.00-25; 385/95-24; 385/95-25	H2715SL	•	104 lbs	•	145 lbs		
16.00-20/21; 17.5-25; 445/80-25	H2724SL			•	142 lbs	•	193 lbs
16.00-24; 16.00-25; 19.5L-24; 445/95-25	H2727SL			•	167 lbs	•	220 lbs
20.5-25; 525/80-25	H2733SL			•	175 lbs	•	261 lbs
18.00-25; 18.00-26; 505/95-25; 600/65-25	H2736SL			•	195 lbs	•	243 lbs
18.00-33	H2742SL			•	232 lbs	•	284 lbs
23.5-25; 25.5-25; 605/80-25	H2745SL					•	300 lbs
21.00-24; 21.00-25	H2748SL					•	298 lbs
21.00-35	H2754SL					•	351 lbs
26.5-25; 686/80-25	H2757SL					•	346 lbs
24.00-25; 26.5-29	H2760SL					•	356 lbs
29.5-25	H2772SL					•	403 lbs
29.5-29	H2775SL					•	427 lbs